

## **Specification Data Sheet**

### **20oz fabric-backed vinyl wallcovering**



#### **Physical Properties**

Total Weight (Avg.) 452g/m<sup>2</sup> (20oz / LY)  
Width (approx.) 132 / 137cm  
Roll Length (approx.) 22.22m  
Fabric Backing Non-woven

#### **Fire Safety**

Class "0" & "1" to BS476, parts 6 & 7  
Euro Class B-s2, d0 to BS EN 13501-1  
Class A to ASTM E-84 Tunnel Test

#### **Bespoke Services**

Custom colours, designs, weights, and micro-venting are available

#### **Environment and Health**

- Highly cleanable. Withstands hospital-grade cleaners & disinfectants when used as directed
- PFOA free – does not contain Perfluorooctanoic Acid
- Cadmium and Mercury free
- Non-Phthalate - Does not contain DEHP Plasticisers
- Low VOC
- Free of PBDE's (Polybrominated Diphenyl Ethers)
- Antimicrobial additives built in

#### **Installation**

Reverse hang / Random match

NB. Some items may have a pattern repeat or special hanging instructions. Please check with Seltex if unsure.

#### **Adhesives & Primers**

Seltex Primer Sealer and Seltex Heavy Adhesive are recommended.  
Seltex Sealed Surface Adhesive (VOV) is also available.

#### **Warranty**

Seltex fabric-backed vinyl wallcoverings are guaranteed to be free of defects in workmanship and material for five years.

© All Seltex designs are copyrighted