

Specification Data Sheet

Seltex Shield semi-rigid wall protection with wear layer



Physical Properties

Total Weight (Avg.)	859 g/m ² (37 oz / LY)
Thickness:	0.863 mm
Width (approx.)	132 / 137cm
Roll Length (approx.)	18.3 m
Fabric Backing	Polyester Cotton - Drill

Fire Safety

Euro Class B-s1, d0 to BS EN 13501-1
Class A to ASTM E-84 Tunnel Test

Features & Benefits

- Maximum Impact Resistance
- Best in class scratch and wear layer
- Comparable to rigid panel performance
- Resistant to chemicals
- Ease of Installation

Environment and Health

- Highly cleanable water-based inks.
- Cadmium and Mercury free
- Phthalate Free
- Low VOC
- Free of PBDE's (Polybrominated Diphenyl Ethers)

Installation

Reverse hang / Random match

NB. Some items may have a pattern repeat or special hanging instructions. Please check with Seltex if unsure.

Adhesives & Primers

Seltex Primer Sealer and Seltex Heavy Adhesive are recommended.
Seltex Sealed Surface Adhesive (VOV) is also available.

Warranty

Seltex fabric-backed vinyl wallcoverings are guaranteed to be free of defects in workmanship and material for five years.

© All Seltex designs are copyrighted