

Specification Data Sheet

Ultra performance contract semi- rigid wall protection with wear layer



Physical Properties

Total Weight (Avg.)	859 g/m ²
Thickness	0.863mm
Width (approx.)	132 / 137 cm
Roll Length (approx.)	18.3 m
Fabric Backing	Polyester Cotton - Drill

Fire Safety

Euro Class B-s1, d0 to BS EN 13501-1
USA Class A to ASTM E-84 Tunnel Test

Features & Benefits

- Maximum Impact Resistance
- Best in class scratch and wear layer
- Comparable to rigid panel performance
- Resistant to chemicals
- Ease of Installation

Environment and Health

- ✓ Highly cleanable water-based inks.
- ✓ Cadmium and Mercury free
- ✓ Phthalate Free
- ✓ Low VOC
- ✓ Free of PBDE's (Polybrominated Diphenyl Ethers)

Installation

Reverse hang / Random match. NB. Some items may have a pattern repeat or special hanging instructions. Please check with Seltex if unsure.

Adhesives & Primers

Seltex Primer Sealer and Seltex Heavy Adhesive are recommended. Seltex Sealed Surface Adhesive (VOV) is also available.

Warranty

Seltex fabric-backed vinyl wallcoverings are guaranteed to be free from defects in materials and workmanship for a period of five (5) years from the date of purchase when installed and maintained in accordance with Seltex recommendations.

Important Notice

All information contained within this document is believed to be accurate at the time of publication and is provided for guidance purposes only. Product colours, textures, finishes, dimensions and performance characteristics may vary within normal manufacturing tolerances and between production batches.

Physical samples should be reviewed and approved prior to final specification, ordering or installation. Specifiers, contractors and purchasers are responsible for determining product suitability for the intended application.

Copyright © Seltex Interiors Limited. All rights reserved.