

SELTEX HEAVY ADHESIVE

WALLCOVERING

Technical Data Sheet

Revised: 01/10/2018

DESCRIPTION

Ready-mixed adhesive especially developed for all kinds of contract wallcovering.

- Very Strong
- Does not stain
- High yield
- Low V.O.C. content
- Contains antibacterial and anti-mould additives

Suitable for:

- Vinyl contract wallcoverings with fabric or non-woven backing, with a weight up to 1kg/m²
- Fibreglass wallcoverings
- Paintable wallcoverings

SURFACE PREPARATION

Surfaces should be sound, dry, clean and free from damp, dust and grease. Any cracks or holes should be filled and high spots sanded level. We always recommend the use of Seltex Primer.

PREPARATION OF ADHESIVE

This adhesive is a ready-to-use product however when necessary, dilute it with clean water up to a maximum of 5%.

APPLICATION

Apply the adhesive in a single coat with a brush or roller. Do not allow adhesive to get onto the face of any wallcovering.

COVERAGE

Approximately 50m² per 10kg tub

CLEANING

Clean possible spills with a damp sponge. The product does not stain.

CONTRAINDICATIONS

This adhesive is not suitable on damp walls with mould or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately.

PACKAGES

10kg Bucket

STORAGE

The product is guaranteed for 24 months from the date of production. Prevent from freezing (keep temperature between 5°C to 40°C)

TECHNICAL DATA

Base:	starch
Physical appearance:	white cream
pH:	6.5
Viscosity:	50,000 to 60,000 cps
V.O.C.:	<0.4 ppm
Percentage of solid:	about 35%
Customs code:	3506 9900
Application temperature:	between 5°C to 40°C
Waiting time:	0-10 minutes
Open time:	20-30 minutes
Setting time:	48 hours
Non-flammable	

FINAL PROVISIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials.

