

DESCRIPTION

Primer / Sealer suitable for surface preparation of walls

- Top efficacy
- High yield
- Low V.O.C. content
- Contains antibacterial and anti-mould additives

SURFACE PREPARATION

Surfaces should be sound, dry, clean and free from damp, dust and grease. Any cracks or holes should be filled and high spots sanded level. Any existing mould should be dealt with and steps taken to prevent future reappearance.

PREPARATION OF THE PRODUCT

Seltex Primer / Sealer has to be diluted with clean water, recommended dilution ratio 1:3 for sealing porous surfaces & 1:1 for priming non-porous surfaces.

APPLICATION

ROLLER/BRUSH - After dilution the primer can be immediately applied to the surface.
The product is usually completely dry in 2/4 hours.

COVERAGE

Approximately 60 - 80 m² per 5 kg tub

CLEANING

We recommend to clean all work tools with water, immediately after the application.

PACKAGES

5kg Plastic tank

STORAGE

The product is guaranteed for 24 months from the date of production. Prevent from freezing (keep temperature between 5°C to 40°C)

TECHNICAL DATA

Base:	acrylic
Physical appearance:	liquid
Colour:	white
pH:	6-7
Viscosity:	2000-3000 cps
V.O.C.:	none
Percentage of solid:	25-28%
Customs code:	3506 1000
Application temperature:	between 5°C to 40°C
Drying time:	2-4 hours
Non-flammable	

FINAL PROVISIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials.